

# INVENTOR INFORMATION

Inventor One Given Name:: Shoji  
Family Name:: KOTANI  
Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.,  
Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chuo-Ku  
City:: Osaka-Shi  
State or Province:: Osaka  
Country:: JAPAN  
Postal or Zip Code:: 541-8556  
City of Residence:: Otsu-Shi  
State or Province of Residence:: Shiga-Ken  
Country of Residence:: JAPAN  
Citizenship Country:: JAPAN  
Inventor Two Given Name:: Hideaki  
Family Name:: UEDA  
Postal Address Line One:: Minolta Co., Ltd., Osaka Kokusai Bldg.  
Postal Address Line Two:: 3-13, 2-Chome, Azuchi-Machi, Chuo-Ku  
City:: Osaka-Shi  
State or Province:: Osaka  
Country:: Japan  
Postal or Zip Code:: 541-8556  
City of Residence:: Kishiwada-Shi  
State or Province of Residence:: Osaka  
Country of Residence:: Japan  
Citizenship Country:: Japan

## CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 24367  
Fax One:: (214) 981-3400  
Electronic Mail One:: pplap@sidley.com  
Electronic Mail Two:: jwwilliams@sidley.com

## APPLICATION INFORMATION

Title Line One:: Recording Method and Recording Apparatus  
Title Line Two:: for Thermoreversible Recording Medium  
Total Drawing Sheets:: 4  
Formal Drawings?:: Yes  
Application Type:: Utility  
Docket Number:: 15162/03460  
Secrecy Order in Parent Appl.?:: No

## REPRESENTATIVE INFORMATION

Representative Customer Number:: 24367

## PRIOR FOREIGN APPLICATIONS

```
Foreign Application One:: 2000-0091611
Filing Date:: 03-29-2000
Country:: JAPAN
Priority Claimed:: Yes

Source:: PrintEFS Version 1.0.1
```

Experiment	Time	Temperature	Pressure	Flow rate	Concentration	Yield	Structure
1	10 min	100 °C	1 atm	10 mL/min	0.1 M	95%	...
2	20 min	120 °C	2 atm	20 mL/min	0.2 M	85%	...
3	30 min	140 °C	3 atm	30 mL/min	0.3 M	75%	...
4	40 min	160 °C	4 atm	40 mL/min	0.4 M	65%	...
5	50 min	180 °C	5 atm	50 mL/min	0.5 M	55%	...
6	60 min	200 °C	6 atm	60 mL/min	0.6 M	45%	...
7	70 min	220 °C	7 atm	70 mL/min	0.7 M	35%	...
8	80 min	240 °C	8 atm	80 mL/min	0.8 M	25%	...
9	90 min	260 °C	9 atm	90 mL/min	0.9 M	15%	...
10	100 min	280 °C	10 atm	100 mL/min	1.0 M	5%	...